



NOTES
 1. CABLE SHIELD WIRES MUST BE GROUNDED AT ENCLOSURE END ONLY USING ITEM 16 PLUG.
 2. KEEP EXTRA CABLE IN ENCLOSURE TO A MINIMUM.

ITEM	PART NO.	QTY	DESCRIPTION
16	C53710-16	1	TIP PLUG ASS'Y
15	A56996	1	TERMINAL NUMBER STICKER
10	C53710-10	5	#6-32NC HEX NUT PER A53567 304SS
9	C53710-9	4	NYLON FLAT WASHER FOR #6 SCREW
8	C53710-8	4	NYLON SPACER .25 OD X .15 ID X .47 LG
7	C53710-7	6'	3 CONDUCTOR SHIELDED WIRE
6	C53710-6	1	SOLENOID CORD W/DIN PLUG
5	C53710-5	1	POWER CORD W/PLUG
4	C53710-4	3	CORD FITTING
3A	STOCK	1	CONNECTOR
3	C53710-3	1	CONTROLLER BOARD LESS CONNECTOR
2C	D52404-5	4	COVER SCREW
2B	D52404-6	1	GASKET
2A	D52404-3	1	COVER
2	D52404-1	1	ENCLOSURE LESS COVER
1	B53415	1	TOUCHPAD OVERLAY

LIST OF MATERIALS

REVISIONS		CHECKED		DRAWING NUMBER		REVISION	
NO.	DESCRIPTION	BY	DATE	SCALE	NO.	DATE	NO.
1	REV FOR VERS 3.0	L/FK	9-5-93	N.T.S.	C53710		A
THE FRED D. PENDING CO. COLUMBUS, OHIO 43212				ASSEMBLY MODEL K CONTROLLER VERSION 3.0 AND HIGHER			