



THE FRED D. PFENING COMPANY
DEDICATED TO THE BAKING
INDUSTRY SINCE 1919
**MODEL B4 DIGITAL
PROOF BOX CONTROL**

The Pfening Model B4 Temperature and Humidity Control features...

- Ease of use
- Bright, large digital display of both temperature and relative humidity
- Highly reliable microprocessor technology
- Ability to lock out set-point changes to unauthorized personnel
- Virtually no maintenance
- Splash proof stainless steel enclosure
- Unlimited settings within humidity range
- Fahrenheit and Celsius temperature scales
- **NEW!!!** – Programmed for modulating valve performance using on-off valves for greater accuracy

The Vaisala HMD60Y Humidity and Temperature Transmitter features...

- Full 0...100% RH measurement
- Accuracy up to $\pm 2\%$ RH
- Excellent accuracy and long-term stability, negligible hysteresis and resistance to dust
- Temperature compensated
- IP65 (NEMA 4) housing



Standard Option on new Pfening systems or upgrade your present equipment

Temperature and Humidity Range:

Temperature: 25° – 122°F or (-)4°C – 50°C
Relative Humidity: 0% - 100%

THE FRED D. PFENING COMPANY
MANUFACTURERS OF
MATERIAL HANDLING, PROOFING,
AND LIQUID METERING SYSTEMS
Visit us at www.pfening.com

1075 WEST FIFTH AVENUE
COLUMBUS, OHIO 43212
PH. (614) 294-5361
FAX (614) 294-1633
email: sales@pfening.com

SPECIFY TO ORDER:

- ELECTRICAL POWER SUPPLY VOLTAGE